

# SuperSheet Foams



**SuperSheet** materials are low-density polyurethane foams featuring excellent water resistance characteristics and physical properties that make them ideal for gasketing and sealing applications.

SuperSheet foams compress with relatively little pressure, allowing their use in lightweight assemblies. With very low compression set, the materials provide an excellent alternative to EPDM seals.

In standard form, SuperSheet foams have a thin water-resistant skin on both upper and lower surfaces. The foams are produced as cast materials

in four standard grades. Standard thicknesses range from 3 mm to 15 mm.

SuperSheet foams provide cost-effective gaskets in a variety of markets and applications, including automotive, marine vehicles, RVs, appliances, cabinetry and small equipment.

- Seal out water and air when compressed 50 to 80 percent
- Resistant to compression set
- Soft, yet strong
- Die cut easily and cleanly
- Available in a variety of thicknesses

<b>Family</b>	<b>Description</b> <i>(sides skinned)</i>	<b>Thick</b>		<b>Size (in)</b> <i>(unless indicated)</i>	<b>Unit</b>	<b>Density</b> <i>(lbsq ft)</i>
		<i>(in)</i>	<i>(mm)</i>			
<b>SUPERSHEET H</b>	1	.12	3	38.19 X 98.4 ft	ROLL	3.8
	1	.16	4	38.19 X 98.4 ft	ROLL	
	1	.20	5	38.19 X 98.4 ft	ROLL	
	1	.24	6	38.19 X 98.4 ft	ROLL	3.4
	2	.32	8	38.19 X 98.4 ft	ROLL	
	2	.40	10	38.19 X 98.4 ft	ROLL	3.2
	1	.60	15	38.19 X 65.6 ft	ROLL	
<b>SUPERSHEET H3</b>	1	.14	3.5	38.19 X 98.4 ft	ROLL	4.0
	1	.20	5	38.19 X 98.4 ft	ROLL	3.8
	2	.30	7.5	38.19 X 98.4 ft	ROLL	
	2	.40	10	38.19 X 98.4 ft	ROLL	3.6
	2	.60	15	38.19 X 65.6 ft	ROLL	
	2	.80	20	38.19 X 65.6 ft	ROLL	
<b>SUPERSHEET H4</b>	2	.20	5	38.19 X 98.4 ft	ROLL	3.7
	2	.24	6	38.19 X 98.4 ft	ROLL	3.6
	2	.32	8	38.19 X 98.4 ft	ROLL	
	2	.40	10	38.19 X 98.4 ft	ROLL	3.5
<b>SUPERSHEET H6</b>	2	.20	5	38.19 X 98.4 ft	ROLL	3.8
	2	.24	6	38.19 X 98.4 ft	ROLL	3.5